

Daisy

Case Features:

- Available for Meat, Fish & Cheese, Salad, Prepared Foods, Deli, Pastry, Bread, Grab-n-Go
- LED light technology enhances presentation
- Available in multiple lengths and glass angles for perfect space planning
- Fully Refrigerated/ Dry/ Neutral
- Choice of Colors/Laminates and Finishes for the front case decoration

Plug Type
(All Models)




6-15P




HEATED

REFRIGERATED


HEATED VENTILATED




DAQV




DAQ




DVM




DSM
Remote only




DVSF



DVS




DCER90




DCIR90

BAIN MARIE




DBM

DRY HEATED DECK




DTA

SALADS




DSLS


GELATO




DGL




DVSG



DVT



DCER45



DCIR45

DISPLAY CASES

Type	Model	Width	Depth	Height	Electrical Requirements	
REFRIGERATED (with Storage)	DVT-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DVT-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps	
	DVT-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DVT-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	Remote only -> DVT-3125	125.4" (3185mm)	42" (1067mm)	47.2" (1200mm)	220V/1Phase/60Hz/14 Amps	
	Remote only -> DVT-3750	150" (3810mm)	42" (1067mm)	47.2" (1200mm)	220V/1Phase/60Hz/13 Amps	
REFRIGERATED (without Storage) DVSG - Pull out Drawer	DVS/DVSG-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/4 Amps	
	DVS/DVSG-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DVS-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps	
	DVS/DVSG-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DVS/DVSG-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	Remote only -> DVS/DVSG-3125	125.4" (3185mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/14 Amps	
	Remote only -> DVS/DVSG-3750	150" (3810mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/13 Amps	
	External 90° Angle	DCER90	42" (1078mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps
	External 45° Angle	DCER45	32.5" (825mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps
	Internal 90° Angle	DCIR90	32.7" (830mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps
Internal 45° Angle	DCIR45	28" (708mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
GELATO	DGL-937 (10 flavors)	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DGL-1250 (14 flavors)	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DGL-1562 (16 flavors)	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	DGL-1875 (20 flavors)	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
SALADS	DSLS-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DSLS-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
GRAB 'N' GO (Refrigerated) DSM - Flat front panel (all models are remote) DVSF - Low Glass (Note: height difference)	DVM/DSM/DVSF-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/4 Amps	
	DVM/DSM/DVSF-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/5 Amps	
	DVM/DSM/DVSF-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/6 Amps	
	DVM/DSM/DVSF-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/7 Amps	
	DVM/DSM/DVSF-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/8 Amps	
	Remote only -> DVM/DSM/DVSF-3125	125.4" (3185mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/14 Amps	
	Remote only -> DVM/DSM/DVSF-3750	150" (3810mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/14 Amps	
	GRAB 'N' GO (Heated)	DAQ-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/9 Amps
	DAQ-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/12 Amps	
HEATED VENTILATED	DAQV-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DAQV-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
DRY HEATED DECK	DTA-1250	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DTA-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
BAIN MARIE	DBM-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DBM-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.