

CLASSIC



CL23



CL24



CL41



CL44



CL441



CL26



CL262



CL71



CL73



CL74



CL92



CL93




CL94


Features:

- Neutral lighting box at the top of the unit
- Option of 1-4 sided views (varies with all models)
- Standard colors available: Silver - Bronze on demand
- Electronic Control of Temperature
- Automatic Defrosting System by using Hot Gas (NFN Series)
- Available:
 - Static Ventilated**
 - No Frost Refrigerated**
 - No Frost Freezer**


CLASSIC




CL26




CL262




CL23 | CL24



CL41 | CL44 | CL441



CL71 | CL73 | CL74



CL92 | CL93 | CL94

CLASSIC - TECHNICAL SPECIFICATIONS

| Type | Model | Temp. Range | Num. of Shelves | Glass Sides | Width | Height | Depths | Electrical Requirements |
|-----------------------|--------|-------------|-----------------|-------------|----------------|--------------|----------------|--------------------------|
| No Frost Refrigerated | CL26R | +50/+23° F | 26 (Rev.) | 4 | 30" (760mm) | 76" (1930mm) | 30" (760mm) | 220V/1Phase/60Hz/5 Amps |
| | CL262R | +50/+23° F | 26 + 26 (Rev.) | 4 | 59" (1500mm) | 76" (1930mm) | 30" (760mm) | 220V/1Phase/60Hz/10 Amps |
| | CL23R | +50/+23° F | 5 (Adj.) | 3 | 18.25" (460mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL24R | +50/+23° F | 5 (Adj.) | 4 | 18.25" (460mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL41R | +50/+23° F | 5 (Adj.) | 1 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL44R | +50/+23° F | 5 (Adj.) | 4 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL441R | +50/+23° F | 7 (Rev.) | 4 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL71R | +50/+23° F | 5 or 3 (Adj.) | 1 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL73R | +50/+23° F | 5 (Adj.) | 3 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL74R | +50/+23° F | 5 (Adj.) | 4 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL92R | +50/+23° F | 5 (Adj.) | 2 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL93R | +50/+23° F | 5 (Adj.) | 3 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL94R | +50/+23° F | 5 (Adj.) | 4 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| No Frost Freezer | CL26F | +41/-13° F | 26 (Rev.) | 4 | 30" (760mm) | 76" (1930mm) | 30" (760mm) | 220V/1Phase/60Hz/5 Amps |
| | CL262F | +41/-13° F | 26 + 26 (Rev.) | 4 | 59" (1500mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/10 Amps |
| | CL23F | +41/-13° F | 5 (Adj.) | 3 | 18.25" (460mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL24F | +41/-13° F | 5 (Adj.) | 4 | 18.25" (460mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL41F | +41/-13° F | 5 (Adj.) | 1 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL44F | +41/-13° F | 5 (Adj.) | 4 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL441F | +41/-13° F | 7 (Rev.) | 4 | 26.5" (670mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL71F | +41/-13° F | 5 or 3 (Adj.) | 1 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL73F | +41/-13° F | 5 (Adj.) | 3 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/10 Amps |
| | CL74F | +41/-13° F | 5 (Adj.) | 4 | 52" (1320mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/10 Amps |
| | CL92F | +41/-13° F | 5 (Adj.) | 2 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL93F | +41/-13° F | 5 (Adj.) | 3 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |
| | CL94F | +41/-13° F | 5 (Adj.) | 4 | 35.5" (900mm) | 76" (1930mm) | 25.25" (640mm) | 220V/1Phase/60Hz/5 Amps |

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.



35 Trade Zone Court ▪ Ronkonkoma, NY 11779 ▪ www.gtidesigns.com
 Phone 631.981.2100 ▪ Fax 631.981.3509 ▪ CustomerService@gtidesigns.com