


Futuro

Case Features:

- Available in: Refrigerated, Bakery, Salads/ Olives, Bain Marie, Meat/ Deli, Pizza, Grab-n-Go
- LED light technology enhances presentation
- Custom color finishing and design options for Interior and End Panel
- Classic European design – simple, stylish, elegant & functional
- Stainless Steel Interior finish
- Offered in various size configurations




REFRIGERATED




FR

BAKERY




FB

DELI




FD (low glass)

MEAT




FM (low glass)

PIZZA




FPN

GRAB 'N' GO




FGGM




FGGL

SALAD/ OLIVES




FS/ FO


BAIN MARIE




FBM




FD (high glass)




FM (high glass)



FPR



FGGH



FGGA

DISPLAY CASES

Type	Model	Width	Depth	Height	Electrical Requirements
REFRIGERATED	FR-1250	49.2" (1250mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FR-1875	73.8" (1875mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FR-2500	98.4" (2500mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
BAKERY	FB-1250	49.2" (1250mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FB-1875	73.8" (1875mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FB-2500	98.4" (2500mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FB-3750	147.6" (3750mm)	43.1" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
SALADS/OLIVES FS/FO	FS/FO-937	37" (937mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FS/FO-1250	49.2" (1250mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FS/FO-1875	73.8" (1875mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FS/FO-2500	98.4" (2500mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FS/FO-3750	147.6" (3750mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FS/FO-90°		43.2" (1096mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
BAIN MARIE	FBM-1250	49.2" (1250mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FBM-1875	73.8" (1875mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FBM-2500	98.4" (2500mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
MEAT/DELI FM/FD	FM/FD-1250	49.2" (1250mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FM/FD-1875	73.8" (1875mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FM/FD-2500	98.4" (2500mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FM/FD-3125	123" (123mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FM/FD-3750	147.6" (3750mm)	51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
90° for deli only →	FM/FD-90		51" (1285mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
PIZZA	FPR-1250	49.2" (1250mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
	FPR-90		43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
Neutral →	FPN-2500	98.4" (2500mm)	43.9" (1115mm)	4.25" (1200mm)	220V/1 Phase/60 Hz/
GRAB 'N' GO FGGH* FGGL* FGGA*	FGGM-1875	73.8" (1875mm)	42" (1060mm)	4.25" (1200mm)/ *	220V/1 Phase/60 Hz/
	FGGM-2500	98.4" (2500mm)	42" (1060mm)	4.25" (1200mm)/ *	220V/1 Phase/60 Hz/
	FGGM-3750	147.6" (3750mm)	42" (1060mm)	4.25" (1200mm)/ *	220V/1 Phase/60 Hz/

Sizing for model numbers * FGGH 5 1.2"(1300mm)/* FGGL 37"(940mm)/ FGGA 51.2"(1300mm)

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.